



LUXPERTEN



LED-Profil





LPIPA 12

LPIPA 16

www.luxperthen.com



LUXPERTEN



Profile LED **LPIPA** / LED-Profil **LPIPA**





	white (lacquered) / weiß (lackiert)	silver (anodized) / silber (eloxiert)
APA 12		
APA 16		
IPA 12		
IPA 16		
Dimensions / Abmessungen	1000 mm, 2020 mm, 3000 mm	
LED strip width / LED-Streifen Breite	up to 12 mm / bis 12 mm	
Application / Anwendungsbereich	surface profiles – for the decorative and wall lighting or for the cove LED lighting / Wand-/ Deckenprofile – zur Beleuchtung von Deckennischen und Dekorationen	



LUXPERTEN

Covers / Abdeckungen

Dimensions / Abmessungen (mm): 1000, 2020, 3000

transparent / transparent	frozen / frostweiß	milky / milchweiß	frosted / frosted	milky frosted / frosted milchweiß	lens 15 / lens 15	lens 30 / lens 30
BASIC						
						
☼ PMMA 95%	☼ PMMA 78%	☼ PMMA 51%	☼ PMMA 90%	☼ PMMA 83%	☼ PMMA 92%	☼ PMMA 92%
☼ PVC 88%	☼ PVC 66%	☼ PVC 44%				
☼ PC 92%	☼ PC 67%	☼ PC 36%				

Maximum dissipated power of LED light sources / Maximale zerstreute Stärke von LED-Lichtquellen		
	for temperature profile / für Profiltemperatur 55 °C	for temperature profile / für Profiltemperatur 65 °C
IPA 12 / IPA 16	31,5 W	42 W
APA 12 / APA 16	32,2 W	43,4 W