


LUXPERTEN



Profil LED

Profile LED / LED-Profil


LPW

www.luxperten.com








LUXPERTEN

Profile LED **LPW** / LED-Profil **LPW**

	white (laquered) Weiß (lackiert)	black (anodized) Schwarz (eloxiert)	inox (anodized) Inox (eloxiert)	silver (anodized) Silber (eloxiert)	raw Roh
					
Dimensions / Abmessungen (mm)	1000, 2020, 3000				
LED strip width (mm) LED-Bandbreite (mm)	Up to 12 / Bis zu 12				
Application Anwendung	recessed profile – for installation in lightweight structures with the use of mounting springs / Einbauprofil - für den Einbau in Leichtbaukonstruktionen unter Verwendung von Montagefedern				

Covers / Abdeckungen

Dimensions / Abmessungen (mm): 1000, 2020, 3000

transparent / Transparent	frozen / Gefroren	milky / Milchig	frosted / Mattiert	milky frosted / Milchig gefror.	Black PMMA / Schwarz	lens 15 / Linse 15	lens 30 / Linse 30
BASIC							
							
✦ PMMA 95%	✦ PMMA 78%	✦ PMMA 51%	✦ PMMA 90%	✦ PMMA 83%	✦ PMMA 23,90%	✦ PMMA 92%	✦ PMMA 92%
✦ PVC 88%	✦ PVC 66%	✦ PVC 44%					
✦ PC 92%	✦ PC 67%	✦ PC 36%					

End caps for **LED profile LPW** (aluminum and plastic)

Endkappen für **LED-Profil LPW** (Aluminium und Plastik)

With a hole / mit Öffnung			
white / Weiß	black / Schwarz	inox / Inox	silver / Silber
BASIC			
			

Accessoires / Zubehör

mounting springs / Montagefedern	Straight connector / Gerader Verbinder	Angular connector 90° / Winkelverbinder 90°	Angular transverse connector / Winkelverbinder	angular connector 120°/ Winkelverbinder 120°	contactless switch / Kontaktloser Schalter
					