


LUXPERTEN




Profil LED

LPB

www.luxperten.com







LUXPERTEN







Profile LED LPB / LED-Profil LPB


Dimensions / Abmessungen (mm): 1000, 2020, 3000

Prolife colors Profil Farben	white (lacquered) / Weiß (lackiert)	black (anodized) / Schwarz (eloxiert)	inox (anodized) / Inox (eloxiert)	silver (anodized) Silber (eloxiert)	raw / Roh
					
1,0 m	10-0021-10	10-0022-10	10-0023-10	10-0024-10	10-0020-10
2,02 m	10-0021-20	10-0022-20	10-0023-20	10-0024-20	10-0020-20
3,0 m	10-0021-30	10-0022-30	10-0023-30	10-0024-30	10-0020-30
LED strip width (mm)	do 12 up to 12				

Covers / Abdeckungen

Dimensions / Abmessungen (mm): 1000, 2020, 3000

transparent / Transparent	frozen / Gefroren	milky / Milchig	milky frosted / Milchig gefroren	black PMMA / Schwarz PMMA	lens 15 / lens 15	lens 30 / lens 30
BASIC						
						
1 m/PMMA 11- 2350-10	1 m/PMMA 11- 2302-10	1 m/PMMA 11- 2251-10	1 m/PMMA 11- 2406-10	1 m/PMMA 11- 2017-10	1 m/PMMA 11- 2060-10	1 m/PMMA 11- 2080-10
1 m/PC 11-3013-10	1 m/PC 11-3012-10	1 m/PC 11-3011-10				



LUXPERTEN

End caps (aluminum and plastic)


Endkappen (Aluminium und Kunststoff)

flat finish / Flache Oberfläche				round finish / Runde Oberfläche			
white / Weiß	black / Schwarz	inox / Inox	silver / gray / Silber / Grau	white / Weiß	black / Schwarz	inox / Inox	silver / gray / Silber / Grau

BASIC							
							
ABS 12-0151-00	ABS 12-0152-00	ABS 12-0153-00	ABS lacq. 12-0000-35 ABS 12-0154-00	ABS 12-0031-00	ABS 12-0032-00	ABS 12-0033-00	ABS lacq. 12-0000-36 ABS 12-0034-00

Accessoires / Zubehör

contactless switch / Kontakloser
Schalter



14-7052-00

Maximum dissipated power of LED light sources

Maximale Verlustleistung von LED-Lichtquellen

for temperature profile / Temperatur für Profil 55° C	for temperature profile / Temperatur für Profil 65° C
17,2 W	22,5 W